

WIRE
SPACERS

PRODUCTS

WIRE SPACERS


S-SCHLANGE

Wire spacer between upper and lower reinforcement mesh.

Snake form ensures high firmness and stability.

No contact to formwork so no risk of corrosion.

certificated type



This product has been tested and certified in accordance with the requirements of the DBV leaflet: „DBV-Merkblatt Unterstützungen“ July 2002

Item-No.	Height mm	Length m	Pcs/Bundle	Pcs/Pallet
UK04A	40	2	25	2.000
UK05A	50	2	25	1.000
UK06A	60	2	25	1.000
UK07A	70	2	25	1.000
UK08A	80	2	25	1.000
UK09A	90	2	25	1.000
UK10A	100	2	25	1.000
UK11A	110	2	25	1.000
UK12A	120	2	25	1.000
UK13A	130	2	25	1.000
UK14A	140	2	25	1.000
UK15A	150	2	25	1.000
UK16A	160	2	25	1.000
UK17A	170	2	25	500
UK18A	180	2	25	500
UK19A	190	2	25	500
UK20A	200	2	25	500
UK22A	220	2	25	400
UK24A	240	2	25	400
UK26A	260	2	25	300
UK28A	280	2	25	300
UK30A	300	2	25	300
UK35A	350	2	25	200
UK40A	400	2	25	200
UK45A	450	2	25	200
UK50A	500	2	25	200

UNTERSTÜTZUNGSKORB

Wire spacer between upper and lower reinforcement mesh.

Ensure high firmness and stability. No contact to formwork so no risk of corrosion.

Item-No.	Height mm	Width mm	Length m	Pcs/ Bundle	Pcs/ Pallet
USK06	60	59	2	200	800
USK08	80	67	2	200	800
USK09	90	71	2	200	800
USK10	100	75	2	200	800
USK11	110	78	2	200	800
USK12	120	82	2	200	800
USK13	130	87	2	200	800
USK14	140	91	2	200	800
USK15	150	95	2	200	800
USK16	160	99	2	200	800
USK17	170	102	2	200	800
USK18	180	106	2	200	400
USK19	190	110	2	200	400
USK20	200	114	2	200	400



This product has been tested and certified in accordance with the requirements of the DBV leaflet: „DBV-Merkblatt Unterstützungen“ July 2002